

PRODUCT SPECIFICATION SHEET

February 2010



MODEL 783

MULTI-VOLTAGE LED WORK LAMP

Model Number

783F-12/48V
783VF-12/48V

Description

12-48V LED Work Lamp – Standard Flood
12-48V LED Work Lamp – Vertical Flood

Applications

- Agriculture
- Industrial
- Utility
- Construction
- Material Handling

Features & Benefits

- Multi-voltage (12-48V) means fewer SKUs
- Standard Flood & Vertical Flood configurations
- Rugged solid state LEDs can withstand shock & vibration
- Long-lasting LEDs mean never having to replace another bulb again!
- Adjustable mounting bracket
- 4-year limited warranty

Product Specifications

- Light Source: Light Emitting Diodes (LEDs)
- Output: Raw: 720 Lumens; Effective: 400 Lumens
- Input Voltage: 12-48V DC
- Current Draw: 1.0 Amps @ 12V; 0.55 Amps @ 24V
0.38 Amps @ 36V; 0.25 Amps @ 48V
- Lens: Polycarbonate
- Housing: Die-Cast Aluminum
- Connector: Integrated 2-Pin Deutsch Weather-Proof Socket (DT04-2P)
- Mounting: Universal Mount; Includes (x1) 3/8-16 x 1" Mounting Bolt
- Mating Connector: 2-Pin Deutsch Weather-Proof Plug (DT06-2S)

Standards Compliance

- ETL Certification
- SAE (DOT) J575 (Sealed, Shock & Vibration)
- SAE (DOT) 1113 (Electromagnetic Interference)
- SAE (DOT) 1455 (Steady State Jumper Starts)
- Sealed to IP67

